

PRODUCT SPECIFICATIONS

STYLE		FIT		SAFETY FEATURES			SOLE CONSTRUCTION			SOLE MATERIAL		SOLE RESISTANCE			STANDARDS			
		Wide Fit	Extra-Wide Fit	Steel ToeCap	Penetration Resistant Midsole	Scuff Guard	Single Density	Dual Density	Goodyear Welt	TPU	Nitrile Rubber	Oil & Acid	Chemical *	Heat Resistant to 130°C	Heat Resistant to 300°C	AS/NZS 2210	EN ISO 20345	EN ISO 17249
Gumboots	Ashley Safety		Y	Y			Y				Y	Y			Y	Y		
	Viking Safety		Y	Y		Y	Y				Y	Y			Y	Y	Y	
	Quatro Safety Non Insulated		Y	Y	Y	Y		Y			Y	Y			Y	Y	Y	
	Quatro Safety Insulated		Y	Y	Y	Y		Y			Y	Y			Y	Y	Y	
	Schöen Forestry Pro		Y	Y			Y	Y			Y	Y	Y		Y	Y	Y	Y
Work Boots	Viking 200	Y		Y				Y		Y			Y				Y	
	Viking 400	Y		Y					Y		Y		Y				Y	
	Red Band® Slip On		Y	Y	Y	Y					Y	Y			Y	Y	Y	
	Red Band® Lace Up		Y	Y	Y	Y					Y	Y			Y	Y	Y	
	Schöen 1000 Nitro		Y	Y	Y	Y					Y	Y			Y	Y	Y	
	Schöen 1100 Pro		Y	Y		Y			Y		Y	Y			Y	Y	Y	Y

* Chemical Resistance - Sole is tested to the requirements of EN 13832 for this component.

For further information on any of the product features or products not listed contact Skellerup Customer Services on 0800 475 355

FOOTWEAR SIZE GUIDE*

MEN'S GUMBOOTS		WOMEN'S/YOUTH GUMBOOTS		CHILDREN'S GUMBOOTS**		JUNIOR GUMBOOTS		MEN'S WORK BOOTS		SCHÖEN 1100 PRO WORK BOOTS	
SIZE	FOOT LENGTH (mm)	SIZE	FOOT LENGTH (mm)	SIZE	FOOT LENGTH (mm)	SIZE	FOOT LENGTH (mm)	SIZE	FOOT LENGTH (mm)	SIZE	FOOT LENGTH (mm)
4	242	3	219	9	161	3c	125	4	237	6	251
5	250	4	230	10	170	4	132	5	244	7	260
6	258	5	237	11	178	5	139	6	253	8	268
7	265	6	248	12	187	6	146	7	261	9	277
8	274	7	255	13	195	7	153	8	271	10	285
9	284	8	263	1	203	8	160	9	280	11	294
10	292	9	270	2	210	9	180	10	290	12	302
11	300					10	187	11	299	13	310
12	309					11	194	12	309		
13	317					12	201	13	318		
14	326					13	208	14	327		
15	334					1	212				
						2	220				
						3	227				

* Please note these measurements relate to length only and do not take into account varying widths.

** Red Band Children's style only.